

Dimensions				
Notes			Specified value	Measured value
	Wheelbase	mm	2580	
Tightening torques				
Notes			Specified value	Measured value
	Tightening torque - steel wheels		80 Nm	
	Tightening torque - alloy wheels		80 Nm	
	Trackrod locknut/clamp		45 Nm	
Checking range - Front wheels				
Notes			Specified value	Measured value
	Load positioning		Unladen	
37	Ride height reference table			
	Toe-in (N = negative, toe-out)	mm	1 - 3	
	Toe-in	deg	0°10' - 0°30'	
	Toe-in	deg-1/100	0,17 - 0,50	
	Camber	deg	0°30'N - 0°30'P	
	Camber	deg-1/100	0,50N - 0,50P	
	Castor	deg	3° - 3°40'	
	Castor	deg-1/100	3 - 3,67	
Setting data - Four wheels				
Notes			Specified value	Measured value
	Load positioning		Unladen	
37	Ride height reference table			
	Toe-in (N = negative, toe-out)	mm	2±1	
	Toe-in	deg	0°20'±10'	
	Toe-in	deg-1/100	0,33±0,17	
	Camber	deg	0°±30'	
	Camber	deg-1/100	0±0,50	
	Camber adjustment		Not adjustable	
	Castor	deg	3°20'±20'	
	Castor	deg-1/100	3,33±0,33	
	Castor adjustment		Not adjustable	
	KPI (SAI)	deg	10°40'±30'	
	KPI (SAI)	deg-1/100	10,67±0,50	
	Included angle	deg	10°40'	
	Included angle	deg-1/100	10,67	
	Rear toe-in	mm	3,40±1	
	Rear toe-in	deg	0°34'±10'	
	Rear toe-in	deg-1/100	0,57±0,17	
	Rear toe-in adjustment		Not adjustable	
	Rear camber	deg	1°20'N±15'	
	Rear camber	deg-1/100	1,33N±0,25	
	Rear camber adjustment		Not adjustable	

Autodata Note 37

	H1	H2
HD	157 mm	160 mm

Fig.74845

Autodata Note 37

	H1	H2
HD	157 mm	160 mm

Fig.74845

